SMART PLUG

Datasheet



SCHUKO



TYPE E

The NodOn® Smart Plug can be controlled through an EnOcean® compliant Home Automation Gateway or directly through others EnOcean® controllers, such as the NodOn® Soft Remote or Wall Switch. It is available in German (Schuko) or French (Type E) standard.

TECHNICAL DATA

Power Source: 230V AC +/-10% - 50Hz
Maximum output power – 3.000W continuous load / 3.500W temporary load (Resistive load)
Self consumption: <1W
Operational temperature – 0°C to 40°C - Altitude – 2.000m
Radio protocol – EnOcean® - 868.3MHz – Bi-directional - EEP – D2-01-0A
Range: 30m indoor
Main power outage detection and notification
Dimensions: 104*51*36mm
Warranty 2 years

STANDARDS

EN61058 2002+AE2008: 2008
NF C 61-314 2008+AE2010: 2010 (Type E)
DIN 0620 -1: 2013 (Schuko)
DIN 0620 -2-1: 2013 (Schuko)
EN301489-1 V1.6.1: 2013
EN301489-2 V1.6.1: 2013
EN300220-1 EN300220-2
V2.4.1: 2012 V1.9.2: 2011

REFERENCES NUMBERS

Product code: ASP-2-1-00 - EAN : 3700313920008 – Type E Version
Product code: ASP-2-1-10 - EAN : 3700313920015 – Schuko Version